

Subdivisions of T. 20 S., R. 9 W.

CHAINS

N.0°3'E., bet. secs. 22 and 23.

Var.20°4'E.

Ascend E. slope of burnt timber slope.

14.00 Enter green fir timber. +150

22.00 A canyon, course E. -60

35.00 Top of spur, bears SE. & NW. +120

40.00 Set a post, 3 ft. long, 3 ins. square, 24 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$  S on W. face; from which

An alder, 3 ins. dia., bears S.60°W., 45 lks. dist., marked  $\frac{1}{4}$  S B T.

A hazel, 2 ins. dia., bears S.45°E., 35 lks. dist., marked  $\frac{1}{4}$  S B T.

52.25 Top of ridge, bears SW. and NE.; begin descent of NW. slope. +250

59.00 A canyon, course NW. -150

Sept. 27th, 1891.

Begin ascent of SE. slope.

74.00 Top of ridge, bears NW. and SE.; begin descent. +200

80.00 A maple, 10 ins. dia., which I marked T 20 S S 14 on NE., R 9 W S 23 on SE., S 22 on SW., S 15 on NW. sides, with 3 notches on S. and 2 notches on E. sides, for cor. to secs. 14, 15, 22 and 23; from which

A fir, 42 ins. diam., bears N.87°E., 16 lks. dist., marked T 20 S R 9 W S 14 B T.

A maple, 12 ins. diam., bears S.30°E., 10 lks. dist., marked T 20 S R 9 W S 23 B T.

A cedar, 15 ins. diam., bears S.51°W., 14 lks. dist., marked T 20 S R 9 W S 22 B T.

A cedar, 16 ins. diam., bears N.6°W., 57 lks. dist., marked T 20 S R 9 W S 15 B T.

N.89°45'W., on random line, bet. secs. 15 and 22.

Var.20°7'E.

40.00 Set temporary  $\frac{1}{4}$  sec. corner.