

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 9 W.

CHAINS		
80.56	Intersect N. & S. line, 30 lks. N. of cor. to secs. 15, 16, 21 and 22. S.89°58'E., on true line, bet. secs. 15 and 22. Va.20°1'E. Ascend S. slope of a timber flat.	
3.00	Begin descent.	+30
13.50	Foot of hill; enter bottom, bears NE. and SW.	-60
14.90	West branch, course SW., 60 lks. wide.	
16.20	Begin steep ascent, leave bottom.	
20.50	Ascent moderates.	
24.75	Top of spur, bears N. & S.; begin descent of N. slope.	+260
28.20	A canyon, course NW.; begin ascent of SW. slope.	-75
34.10	Top of spur, bears N. & S. Cain's house bears N.40°E. Begin descent of N. slope.	+120
40.28	Set a post, 3 ft. long, 3 ins. square, 18 ins. in the ground, for 1/4 sec. cor., marked 1/4 S on N. face; from which A fir, 30 ins. diam., bears N.54°W., 50 lks. dist., marked 1/4 S B T. A cedar, 15 ins. diam., bears S.49 1/2°E., 42 lks. dist., marked 1/2 S B T. A cliff, 6 ft. high, is S. 10 lks.	-60
40.75	Begin ascent.	
45.00	Top of spur, bears N. & S.	+70
49.60	A canyon, course N.	-90
54.00	Top of spur; begin steep descent.	-120
60.25	A canyon, course N.; begin ascent.	-100
78.75	Top of ridge, bears SE. and NW.	+375
80.56	The cor. of secs. 14, 15, 22 and 23. Sept. 29th, 1891.	

N.0°3'E., bet. secs. 15 and 14.  
Va.20°8'E.  
Descend E. slope.