

County Surveyor's Record, Douglas County, Oregon

347

Subdivisions of T. 20 S., R. 9 W.

CHAINS		
3.00	Foot of descent; begin ascent.	-50
7.50	Top of spur, bears E. & W.; begin descent.	+40
9.00	A canyon, course E.; begin ascent.	-60
13.50	Top of spur, bears E. & W.; begin descent.	+100
20.00	A gulch, course E.; begin ascent.	-80
22.50	Top of spur, bears E. & W.; the line runs near the top of ridge, since begun.	+40
27.00	Top of ridge, bears N. & S.	-50
28.75	Begin steep descent; recross ridge to E. slope.	
34.40	A gulch, course E.; begin ascent.	-175
38.75	Top of spur, bears E. & W.; descend.	+35
40.00	Set a post, 3 ft. long, 4 ins. square, 24 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on W. face; from which <p style="margin-left: 40px;">A fir, 20 ins. diam., bears S.75$\frac{1}{2}$°W., 18 lks. dist., marked $\frac{1}{4}$ S B.T. A fir, 45 ins. diam., bears N.47°E., 29 lks. dist., marked $\frac{1}{4}$ S B.T.</p> Keep descending.	
46.50	A branch, 6 lks. wide, course W.	-120
47.00	Helmic's house bears W. Through burnt timber flat.	
57.40	A gulch, course W.; pass along W. slope.	
65.50	West branch, 100 lks. wide, course S.20°W.	
67.25	Enter bottom.	
73.75	West branch, 80 lks. wide, course SE. Enter cleared bottom.	
80.00	Set a post, 5 ft. long, 6 ins. sq., 24 ins. in the ground, for cor. to secs. 10, 11, 14, and 15, marked T 20 S S 11 on NE., R 9 W S 14 on SE., S 15 on SW., S 10 on NW. faces, with 4 notches on S. and 2 notches on E. edges; from which <p style="margin-left: 40px;">A fir, 42 ins. diam., bears N.59$\frac{1}{2}$°E., 62 lks. dist., marked T 20 S R 9 W S 11 B T. A fir, 36 ins. diam., bears S.86$\frac{1}{2}$°E., 86 lks. dist.,</p>	