

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 9 W.

CHAINS

marked T 20 S R 9 W S 14 B T.

A fir, 36 ins. diam., bears S.29°W., 54 lks. dist.,

marked T 20 S R 9 W S 15 B T.

A fir, 15 ins. diam., bears N.42°W., 53 lks. dist.,

marked T 20 S R 9 W S 10 B T.

N.89°58'W., on random line, bet. secs. 10 & 15.

Va.20°3'E.

40.00 Set temporary 1/4 sec. corner.

80.80 Intersect N. & S. line, 24 lks. N. of cor. to secs. 9, 10, 15, and 16.

Sept. 30th, 1891.

Thence I run

N.89°52'E., on true line, bet. secs. 10 & 15.

Ascend S. slope.

2.00 Top of ridge, bears SW. & NE.; begin descent of SE. slope. +75

11.00 Foot of descent; begin ascent. -80

16.50 Top of spur, bears N. & S.; descend N. slope. +40

31.00 A rocky canyon, course NE. -500

34.00 Top of a rocky spur, bears N. & S.; begin steep descent.

40.40 Set a post, 3 ft. long, 3 ins. square, 24 ins. in the ground, for 1/4 sec. cor., marked 1/4 S on N. face; from which

A maple, 12 ins. dia., bears S.87 1/2°W., 66 lks. dist., marked 1/4 S B T.

A cedar, 10 ins. dia., bears N.31 1/2°E., 31 lks. dist., marked 1/4 S B T.

40.90 A canyon, course N. -20

42.25 Top of rise; begin descent. +60

48.75 A rocky canyon, course S.80°E. -40

53.00 Top of rise. +50

54.25 A branch, 10 lks. wide, course S.; begin steep ascent. -60

62.50 Top of spur, bears N. & S.; begin steep descent. +230

70.40 West branch, 60 lks. wide, course S. -200

71.00 Enter cleared bottom.