

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 9 W.

CHAINS

A fir, 30 ins. dia., bears S.86°W., 27 lks. dist.,  
marked T 20 S R 9 W S 10 B T.

A vinemaple, 6 ins. dia., bears N.17°W., 7 lks.  
dist., marked T 20 S R 9 W S 3 B T.

Oct. 3rd, 1891.

N.0°3'E., bet. secs. 2 and 3.

Var.20°8'E.

4.50	Top of ridge, bears E. & W.; begin descent.	+100
9.75	A canyon, course NE.; begin ascent.	-240
18.50	Top of spur, bears E. & W.; begin descent.	+150
24.10	A creek, 10 lks. wide, bears SE.; begin ascent.	-90
30.50	Top of spur, bears N. & S.; begin descent.	+100
32.50	A canyon, course SW.; begin ascent of SW. slope.	-30
40.00	Set a post, 3 ft. long, 3 ins. square, 18 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on W. face; from which An alder, 6 ins. diam., bears S.52°E., 37 lks. dist., marked $\frac{1}{4}$ S B T. A fir, 40 ins. diam., bears N.25°W., 28 lks. dist., marked $\frac{1}{4}$ S B T. Ascend SW. slope.	
44.50	Top of rise; begin descent.	+200
48.00	Foot of descent; begin steep ascent.	
52.00	More moderate ascent.	
57.50	Top of ridge, bears SW. and NE.; begin steep descent.	+250
65.00	A canyon, course SE.; begin ascent of W. slope.	-175
72.50	Top of ridge, bears N.70°W. and S.70°E.; begin steep descent.	+150
80.00	To corner to secs. 2, 3, 34 & 35, described in book of exteriors.	-30

Oct. 5th, 1891.

I return to cor. of secs. 25, 26, 35, and 36; thence I  
run