

Subdivisions of T. 20 S., R. 9 W.

CHAINS

N.4'E., bet. secs. 25 and 26.

Va.20°8'E.

Ascend burnt rocky S. slope.

- 4.00 Top of rocky ridge, bears E. & W.; very steep descent of rocky cliff. +75
- 20.75 Smith River, 100 lks. wide, course W., 18 ins. deep; enter bottom. -50
- 25.50 Begin ascent of brushy S. slope.
- 27.00 Enter small fir timber. +250
- 40.00 Set a post, 4 ft. long, 5 ins. square, 24 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on W. face; from which +120
- A fir, 36 in. dia., bears N.51°W., 20 lks. dist., marked $\frac{1}{4}$ S B T.
- A fir, 42 ins. dia., bears N.83°E., 45 lks. dist., marked $\frac{1}{4}$ S B T.
- This post stands almost on top of a flat ridge; small timber has been burnt and now covers the ground.
- Ascend slightly.
- 54.00 A cedar, 48 in. in dia., which I marked with 2 notches on N. & S. sides.
- 64.25 A branch, 1 lk. wide, course SW.; begin steeper ascent. +90
- 72.20 Top of spur, bears NE. & SW.; begin steep descent through mostly green cedars, no fallen timber. +180
- 76.50 A canyon, course W.; begin ascent through green timber. -240
- 80.00 Set a post, $4\frac{1}{2}$ ft. long, 4 ins. square, 24 ins. in the ground, for cor. to secs. 23, 24, 25 & 26, marked T 20 S S 24 on NE., R 9 W S 25 on SE., S 26 on SW., S 23 on NW. faces, with 1 notch on E. and 2 notches on S. edges; from which
- A cedar, 15 ins. diam., bears N.66°E., 50 lks. dist., marked T 20 S R 9 W S 24 B T.
- A cedar, 12 ins. diam., bears S.43°E., 31 lks. dist., marked T 20 S R 9 W S 25 B T.
- A cedar, 8 ins. diam., bears S.58°W., 9 lks. dist.