

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 9 W.

CHAINS

N.0°4'E., bet. secs. 23 and 24.

Va.20°8'E.

Ascend through fallen timber with little green timber standing.

12.50 Top of a ridge, bears SW. and NE.; begin descent. +240

16.00 A canyon, course SW. -100

21.50 Top of spur, green timber. +120

27.00 A canyon and branch, 2 lks. wide, course SW.; begin ascent. -80

40.00 Set a post, 3 ft. long, 3 ins. square, 18 ins. in the ground, for 1/4 sec. cor., marked 1/4 S on W. face; from which

An alder, 3 ins. dia., bears N.47°W., 63 lks. dist., marked 1/4 S B T.

An alder, 4 in. dia., bears S.66°W., 35 lks. dist., marked 1/4 S B T.

Keep ascending.

48.00 Top of ridge, bears E. & W.; begin descent. +400

57.50 A canyon and branch, 1 lk. wide, course N.60°E.; begin ascent. -120

68.25 Top of ridge, bears SE. and NW. +240

74.60 A canyon, course E. -150

80.00 Set a cedar post, 4 ft. long, 4 ins. square, 24 ins. in the ground, for cor. to secs. 13, 14, 23 & 24, marked T 20 S S 13 on NE., R 9 W S 24 on SE., S 23 on SW. and S 14 on NW. faces, with 1 notch on E. and 3 notches on S. edges; from which

A cedar, 8 ins. dia., bears N.6°E., 84 lks. dist., marked T 20 S R 9 W S 13 B T.

A cedar, 60 ins. dia., bears S.74°E., 19 lks. dist., marked T 20 S R 9 W S 24 B T.

A vinemaple, 4 ins. dia., bears S.60°W., 55 lks. dist., marked T 20 S R 9 W S 23 B T.

A cedar, 36 ins. dia., bears N.77°W., 71 lks. dist., marked T 20 S R 9 W S 14 B T.

Oct. 14th, 1891.