

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 9 W.

CHAINS

East, on true line, bet. secs. 13 and 24.

Var. 20° 8' E.

Follow down a canyon, course E.

- 6.00 Ascend N. slope.
- 13.50 Top of spur, bears SE. & NW. +180
- 21.25 A branch, 2 lks. wide, in a canyon, course S. 75° E.; begin ascent of S. slope. -150
- 37.00 Top of ridge, bears SE. & NW. +200
- 40.00 Set a post, 3 ft. long, 3 ins. square, 18 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$  S on N. face; and raised a mound of stone,  $1\frac{1}{2}$  ft. high and 2 ft. base, alongside. Pits impracticable.
- 53.00 A canyon, course SE.; begin ascent. -140
- 62.00 Top of spur, bears SE. & NW. +120
- 74.50 A canyon, course SE.; begin ascent. -100
- 87.00 Top of ridge, bears NE. & SW. +180
- 92.50 A canyon, course E. -80
- 99.10 Intersect East boundary of township, 140 lks. South of  $\frac{1}{4}$  sec. cor. bet. secs. 13 and 18, which is a post, 4 ins. square, marked  $\frac{1}{4}$  S on W. face; from which
  - A fir, 18 ins. dia., bears N. 71° W., 10 lks. dist., marked  $\frac{1}{4}$  S B T.
  - A fir, 20 ins. dia., bears S. 70° E., 15 lks. dist., marked  $\frac{1}{4}$  S B T.

I set a sandstone, 11x8x6 ins., 8 ins. in the ground, for closing cor. to secs. 13 and 24, marked C C with 3 notches on S. & N. edges; and raised a mound of stone,  $1\frac{1}{2}$  ft. high and 2 ft. base, alongside. Pits impracticable.

October 16th, 1891.

N. 0° 4' E., bet. secs. 13 and 14.

Var. 20° 8' E.

Descend.

- .30 A canyon, course E.; begin ascent.
- 3.75 A cliff; very steep ascent.