

Subdivisions of T. 20 S., R. 9 W.

CHAINS 10.50	A spur, bears NE. & SW.; begin descent.	+280
13.00	A canyon, course NE.	-100
15.20	Top of spur, bears E. & W.; begin descent.	+60
17.50	A canyon, course SE.; begin ascent.	-90
23.50	Top of spur, bears E. & W.; begin descent.	+150
27.75	Foot of gulch, course SW.; begin ascent.	
29.50	Top of ridge, bears NE. & SW.; begin descent of west slope.	
40.00	Set a post, 3 ft. long, 3 ins. square, 18 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on W. face; from which  A fir, 50 in. dia., bears N.47°E., 27 lks. dist., marked $\frac{1}{4}$ S B T.  A fir, 30 in. dia., bears S.40°W., 56 lks. dist., marked $\frac{1}{4}$ S B T.  Ascend.	-220
44.50	Top of ridge, bears S.20°E. & N.20°W.; begin descent.	+150
55.00	A canyon, course NW.	-100
60.50	Top of spur, bears E. & W.; begin descent.	+140
63.60	A canyon, course W.; begin ascent.	-150
72.50	Top of ridge, bears E. & W.; begin steep descent.	+250
79.00	A canyon, course NW.	-175
80.00	Set a post, 5 ft. long, 5 ins. square, 24 ins. in the ground, for cor. to secs. 11, 12, 13 & 14, marked T 20 S S 12 on NE., R 9 W S 13 on SE., S 14 on SW., S 11 on NW. faces, with 1 notch on E. and 4 notches on S. edges; from which  A fir, 24 ins. dia., bears N.43 $\frac{1}{2}$ °E., 26 lks. dist., marked T 20 S R 9 W S 12 B T.  A fir, 33 ins. dia., bears S.55 $\frac{3}{4}$ °E., 27 lks. dist., marked T 20 S R 9 W S 13 B T.  A fir, 30 ins. dia., bears S.5°W., 140 lks. dist., marked T 20 S R 9 W S 14 B T.  A fir, 36 ins. dia., bears N.3 $\frac{1}{2}$ °W., 55 lks. dist., marked T 20 S R 9 W S 11 B T.	

October 17th, 1891.