

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 9 W.

CHAINS	N.89°45'W., on random line, bet. secs. 11 and 14. Va.20°8'E.	
40.00	Set temporary $\frac{1}{4}$ sec. cor.	
80.42	Intersect N. & S. line, 40 lks. N. of cor. to secs. 10, 11, 14 and 15. Thence I run N.89°58'E., on true line, bet. secs. 11 & 14. Va.20°2'E.	
1.00	Begin steep ascent.	
5.00	Top of a gentle ascending timber flat, bears N. & S.	+75
20.00	Begin steep ascent of SW. slope.	
29.00	Top of ascent; begin steep descent.	+140
40.00	West branch. Set a sandstone, 36x18x6 ins., 24 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on N. face; raised a mound of stone, 1 $\frac{1}{2}$ ft. high, 2 ft. base, alongside; from which A maple, 24 ins. dia., bears N.79 $\frac{1}{4}$ °E., 102 lks. dist., marked $\frac{1}{4}$ S B T. A fir, 24 ins. dia., bears S.75 $\frac{1}{2}$ °E., 215 lks. dist., marked $\frac{1}{4}$ S B T. Cross West branch, course NW., 75 lks. wide; enter bottom, bears NW. & SE.	
45.00	Begin ascent.	
49.00	Top of ascent.	+60
59.00	Enter bottom, bears NE. and SW.	
63.10	West branch, 75 lks. wide, course SW.; begin steep ascent of NW. slope.	
68.00	W. Wroe's house bears N.6°W., about 11 chains dist.	
74.10	Top of spur, bears N. & S.; begin steep descent.	+350
78.75	A canyon, course N.; begin steep ascent.	-110
80.42	The cor. of secs. 11, 12, 13 & 14.	

October 20th, 1891.

East, on true line, bet. secs. 12 and 13.
Va.20°8'E.
Ascend.