

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 9 W.

CHAINS		
	Ascend W. slope.	
4.00	Top of spur, bears N. & S.; begin steep descent.	
7.00	A canyon, course NW.; begin ascent.	-80
14.25	Top of spur, bears N. & S.; begin steep descent.	+120
20.75	A canyon, course W.; begin ascent.	-80
25.50	Top of spur, bears E. & W.; begin descent.	+130
32.80	A cedar, 36 ins. dia., which I marked with 2 notches on N. & S. sides.	
	B. Wroe's house bears S.44°W. Enter bottom.	
40.00	Set a post, 4 ft. long, 4 ins. square, 24 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on W. face; from which A fir, 36 ins. dia., bears S.9°W., 56 lks. dist., marked $\frac{1}{4}$ S B T. A fir, 40 ins. dia., bears S.28°E., 54 lks. dist., marked $\frac{1}{4}$ S B T.	-150
	Through bottom.	
48.00	West branch, course S.30°W., 60 lks., wide.	
50.00	Begin ascent.	
58.50	Ascent becomes more steep.	
63.80	Top of spur, bears E. & W.; begin descent.	
72.10	A canyon, course E.; begin ascent.	
77.00	Top of timber bench, bears E. & W.	
80.00	Set a post, 4 ft. long, 4 ins. square, 24 ins. in the ground, for cor. to secs. 1, 2, 11 & 12, marked T 20 S S 1 on NE., R 9 W S 12 on SE., S 11 on SW. and S 2 on NW. faces, with 1 notch on E. and 5 notches on S. edges; from which A fir, 24 ins. dia., bears N.88°E., 15 lks. dist., marked T 20 S R 9 W S 1 B T. A vinemaple, 4 ins. dia., bears S.32°E., 18 lks. dist., marked T 20 S R 9 W S 12 B T. A fir, 15 ins. dia., bears S.47°W., 34 lks. dist., marked T 20 S R 9 W S 11 B T. A fir, 24 ins. dia., bears N.29°W., 4 lks. dist.,	