

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 9 W.

CHAINS
80.56

The cor. to secs. 1, 2, 11 & 12.

October 27th, 1891.

Resurvey of the S. Bdy. of T. 20 S., R. 9 W.
by Alonzo Gesner under Contract 608 dated Apr. 17, 1893.

Commencing at the cor. to Tps. 20 S., Rs. 9 and 10 W.,
which is a post, 5 ins. sq., 2 ft. above ground, on
steep hillside, sloping nearly North, marked T 20 S S 31
on the NE., R 9 W S 6 on the SE., T 21 S S 1 on the SW.
and R 10 W S 36 on the NW. faces, with 6 notches on the
N., E., S. and W. edges; from which

A maple, 14 ins. diam., bears N.64°E., 69 lks. dist.,
marked T 20 S R 9 W S 31 B T.

A maple, 14 ins. diam., bears S.12°30'E., 49 lks.
dist., marks had been obliterated.

A fir, 36 ins. diam., bears S.33°15'W., 44 lks. dist.,
marks grown over.

A fir, 24 ins. diam., bears N.32°15'W., 70 lks. dist.,
marked T 20 S R 10 W S 36 B T.

Substantially agreeing with notes supplied me by the
U. S. Sur. General.

Thence I run

East, on south bdy. of Sec. 31.

Va. 20°E.

Descend.

8.50 Creek, 10 lks. wide, c North; pass over spur.

18.00 Left bank of Smiths River. To get distance across river
I set flag; thence over river and in line on South Bdy.
of Sec. 31, on the right bank of the river. I run
North 200 lks. for base when I find the flag bears
S.71°34'W., which gives by Nat. Cot. x base or 2.9714
 x 2.00 makes 5.94 chs. across river; add to this the
distance to river, 18.00 chs., makes

23.94 To the right bank of river.

40.00 To point for $\frac{1}{2}$ sec. cor. All traces of it had been de-