

Resurvey of S. Bdy. of T. 20 S., R. 9 W.

CHAINS

A hemlock, 30 ins. diam., bears N.37°E., 68 lks. dist., marked T 20 S R 9 W S 34 B T.

A hemlock, 12 ins. diam., bears S.21°E., 36 lks. dist., marked T 21 S R 9 W S 3 B T.

An alder, 18 ins. diam., bears S.63°30'W., 67 lks. dist., marked T 21 S R 9 W S 4 B T.

A fir, 30 ins. diam., bears N.14°W., 46 lks. dist., marked T 20 S R 9 W S 33 B T.

Practically agreeing with notes furnished me by the U. S. Sur. General.

East, on the S. bdy. of Sec. 34.

Va.20°E.

0.48 A cedar, 40 ins. diam., marked with 2 notches on the E. and W. sides.

12.00 Top of spur, sloping NW.; descend. +250

27.35 Creek, 15 lks. wide, c N.65°W. -150

41.25 To a point 34 lks. S. of the $\frac{1}{4}$ sec. cor., which is a fir, 40 in. diam., marked $\frac{1}{4}$ S on the N. side; from which
A fir, 20 ins. diam., bears S.88°W., 72 lks. dist., marked $\frac{1}{4}$ S B T.

A cedar, 16 ins. diam., bears N.46°E., 70 lks. dist., marked $\frac{1}{4}$ S B T.

Continued East from the $\frac{1}{4}$ sec. cor.

65.00 Top of ridge, c N. and S.; descend. +400

82.15 To a point 38 lks. S. of the corner to secs. 34 and 35, which is a fir tree, 18 ins. diam., marked T 20 S S 35 on the NE., R 9 W on the SE. sides; from which

An alder, 15 ins. diam., bears N.47°E., 56 lks. dist., marked T 20 S R 9 W S 35 B T.

A maple, 12 ins. diam., bears S.28°E., 33 lks. dist., marked T 21 S R 9 W S 2 B T.

A fir, 18 ins. diam., bears S.25°30'W., 40 lks. dist., marked T 21 S R 9 W S 3 B T.

A fir, 42 ins. diam., bears N.22°W., 75 lks. dist., marked T 20 S R 9 W S 34 B T.