

Resurvey of S. Bdy. of T. 20 S., R. 9 W.

CHAINS

stone, 8x10x6 ins. above the ground, marked  $\frac{1}{4}$  on the N. side; from which

A fir, 24 ins. diam., bears N.52 $\frac{1}{2}$ °W., 46 lks. dist., marked  $\frac{1}{4}$  S B T.

A fir, 30 ins. diam., bears S.87°E., 29 lks. dist., marked  $\frac{1}{4}$  S B T.

Continued East from the  $\frac{1}{4}$  sec. cor.

45.00 Top of ridge, c N. and S.; descend. +150

81.00 Creek, 1 lk. wide, c North; ascend. -125

95.23 To a point 57 lks. S. of the closing cor. to Tps. 20 and 21 S., R. 9 W., which is a stone, 5x8x7 ins. above ground, marked C C on the E. side, with 6 notches on the S., W. and N. sides; a small stone mound alongside.

Whole length of line 95.23 chs.

The true course from the cor. to secs. 35 and 36 to the C. C. is S.89°12'E.

Note: The lines on Secs. 31, 32, and 33 were not blazed; the lines on Secs. 34, 35, and 36 were well blazed.

Portion of S. Bdy. of T. 19 S., R. 9 W. as surveyed by Henry L. Chandler under Contract 705 dated Apr.14,1899.

East, on S. bdy. of Sec. 34.

\* \* \* \* \*

80.00 The cor. to secs. 34 and 35, established on former survey, which is a fir post, 3 ft. long, 4 ins. sq., set 24 ins. in the ground, marked T 19 S S 35 on NE. and R 9 W S 34 on NW. faces, with 2 notches on E. and 4 notches on W. edges; from which

A fir, 22 ins. diam., bears N,55 $\frac{1}{2}$ °E., 20 lks. dist., marked T 19 S R 9 W S 35 B T.

A fir, 16 ins. diam., bears N,5°W., 54 lks. dist., marked T 19 S R 9 W S 34 B T.

July. 12, 1899.

East, on S. bdy. of Sec. 35.