

County Surveyor's Record, Douglas County, Oregon

Portion of S. Bdy. of T. 19 S., R. 9 W.

CHAINS

Ascend through heavy timber & dense undergrowth.

0.87 The old cor. of secs. 2 and 3, T. 20 S., R. 9 W., which is a post, marked and witnessed as described by the surveyor general. The markings referring to secs. on N. were obliterated on my former survey.

6.50 Top of spur, 100 ft. above sec. cor., bears NE.; descend 300 ft. to

25.00 Ravine, course S.; ascend 200 ft. to

39.00 Top of spur, bears SE.; descend.

40.00 The 1/4 sec. cor. established on former survey, which is an alder, 8 ins. diam., marked 1/4 S 35 on N. side; from which

A cedar, 10 ins. diam., bears N.61°E., 35 lks. dist., marked 1/4 S B T.

An alder, 7 ins. diam., bears S.28°E., 18 lks. dist., marked 1/4 S B T.

41.05 The old 1/4 sec. cor. on N. bdy. of Sec. 2, T. 20 S., R. 9 W., which is a chittem tree, 6 in. diam., marked and witnessed as described by the surveyor general.

45.65 Beaver Creek, 12 lks. wide, 100 ft. below top of spur, course S.; ascend 80 ft. to

48.00 Top of spur, bears SW.; descend 50 ft. to

49.00 Ravine, course SW.; ascend 200 ft. to

80.00 Summit of ridge, bears NW. and SE.

Set a post, 3 ft. long, 4 ins. sq., 24 ins. in the ground, cor. of secs. 35 and 36, marked T 19 S S 36 on NE. and R 9 W S 35 on NW. faces, with 1 notch on E. and 5 notches on W. edges; from which

A cherry, 7 ins. diam., bears N.82 1/2°E., 30 lks. dist., marked T 19 S R 9 W S 36 B T.

A cherry, 8 ins. diam., bears N.63°W., 22 lks. dist., marked T 19 S R 9 W S 35 B T.

Old cor. bears E. 4 lks. dist.; I destroy it.

East, on S. bdy. of Sec. 36.