

County Surveyor's Record, Douglas County, Oregon

Retracement and Resurvey of Portion of North Bdy. of T. 20 S., R. 9 W.

CHAINS  
340.46

Fall 22.41 chs. N. of the closing cor. of Tps. 19 and 20 S., R. 9 W.

From this cor. I retrace East, making diligent search, but finding no evidence of line or corners.

The true bearing and distance from the closing cor. of Tps. 19 and 20 S., R. 9 W. to the cor. of secs. 34 and 35, T. 19 S., R. 9 W. is N.86°14'E., 341.20 chs.

From the closing cor. of Tps. 19 and 20 S., R. 9 W., heretofore described,

N.86°14'E., resurveying S. bdy. of Sec. 31, T. 19 S., R. 9 W.

Over mountainous land, through heavy timber and dense undergrowth.

Ascend 175 ft. on W. slope.

- 6.00 Ridge, bears NE. and SW.; descend 200 ft. on SE. slope.
- 11.90 Ravine, course S.; ascend 25 ft. on SW. slope.
- 13.90 Spur, slopes S.; descend 150 ft. on SE. slope.
- 17.50 Ravine, course SE.; ascend 100 ft. on SW. slope.
- 20.50 Spur, slopes S.; descend 120 ft. on SE. slope.
- 23.00 Ravine, course SE.; ascend 180 ft. on SW. slope.
- 33.00 Spur, slopes SE.; descend 250 ft. on E. slope to
- 42.65 (Apportioned distance) Set an iron post, 3 ft. long, 1

in. diam., 27 ins. in the ground, for 1/4 sec. cor. of sec. 31 only, with brass cap marked

1831  
1921

from which

An alder, 28 ins. diam., bears N.19°E., 30 lks. dist., marked 1/4 S 31 B T.

A fir, 14 ins. diam., bears N.83°W., 28 lks. dist., marked 1/4 S 31 B T.

Descend 270 ft. on E. slope.

- 51.05 Creek, 8 lks. wide, course NE.; ascend 100 ft. on W. slope.