

Retracement and Resurvey of Portion of North Bdy.
of T. 20 S., R. 9 W.

CHAINS

54.35 Spur, slopes NW.; thence over N. slope.
60.22 Point at 40.00 chs. westing from closing cor. of secs. 5,
and 6, determined as hereinafter set forth.
Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the
ground, for $\frac{1}{4}$ sec. cor. of sec. 6 only, with brass cap
marked

186
1921

from which

A cedar, 9 ins. diam., bears S.83°E., 59 lks. dist.,
marked $\frac{1}{4}$ S 6 B T.

A cedar, 45 ins. diam., bears S.78°W., 61 lks. dist.,
marked $\frac{1}{4}$ S 6 B T.

62.15 Creek, 1 lk. wide, course NW.; ascend 110 ft. on SW.slope.

65.90 Ravine, course SW.; ascend 400 ft. on W. slope.

73.90 Ridge, bears N. and S.; descend 180 ft. on NE. slope.

83.35 Ravine, course NW.; ascend 50 ft. on W. slope to

85.30 (Apportioned distance) Set an iron post, 3 ft. long, 2
ins. diam., 27 ins. in the ground, for cor. of secs.
31 and 32, T. 19 S., R. 9 W., with brass cap marked

T19S | R9W
S31 | S32
T20S R9W
S6
1921

from which

A fir, 12 ins. diam., bears N.26°E., 30 lks. dist.,
marked T 19 S R 9 W S 32 B T.

A maple, 18 ins. diam., bears N.24°W., 41 lks. dist.,
marked T 19 S R 9 W S 31 B T.

N.86°14'E., resurveying S. bdy. of Sec. 32, T. 19 S., R.
9 W.

Over mountainous land, through heavy timber and dense
undergrowth.

Ascend 200 ft. on W. slope.

6.50 Ridge, bears NE. and SW.; descend 180 ft. on SE. slope.