

## County Surveyor's Record, Douglas County, Oregon

## Resurvey of Portion of North Bdy. of T. 20 S., R. 9 W.

CHAINS

11.00 Draw, course SW.; ascend 45 ft. on W. slope to  
 15.01 Point of intersection with line bet. secs. 5 and 6, deter-  
 mined as hereinafter set forth.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in  
 the ground, for closing cor. of secs. 5 and 6, with  
 brass cap marked

T19S	R9W
S32	
-----	
S6	S5
T20S	R9W
CC	
1921	

from which

A vine maple, 5 ins. diam., bears S.68°E., 19 lks.  
 dist., marked T 20 S R 9 W S 5 C C B T.

A fir, 30 ins. diam., bears S.18°W., 31 lks. dist.,  
 marked T 20 S R 9 W S 6 C C B T.

Descend 380 ft. on SE. slope.

24.00 Ravine, course SE.; ascend 100 ft. on SW. slope.

31.00 Spur, slopes SE.; descend 390 ft. on E. slope to

42.65 (Apportioned distance) Set an iron post, 3 ft. long, 1  
 in. diam., 27 ins. in the ground, for re-established  $\frac{1}{2}$   
 sec. cor. of sec. 32 only, with brass cap marked

<u>1/2 S 32</u>	
1921	

from which

A fir, 36 ins. diam., bears N.38°E., 88 lks. dist.,  
 marked  $\frac{1}{2}$  S 32 B T.

An alder, 24 ins. diam., bears N.27°W., 33 lks. dist.,  
 marked  $\frac{1}{2}$  S 32 B T.

Descend 30 ft. on E. slope.

43.80 Creek, 6 lks. wide, course NE.; ascend 400 ft. on W.  
 slope to

55.06 Midpoint on N. bdy. of sec. 5, determined as hereinafter  
 set forth.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in  
 the ground, for  $\frac{1}{2}$  sec. cor. of sec. 5 only, with brass  
 cap marked