

Resurvey of Portion of North Bdy. of T. 20 S., R. 9 W.

CHAINS

435
1921

from which

A fir, 14 ins. diam., bears S.78°E., 41 lks. dist.,
marked $\frac{1}{2}$ S 5 B T.

An alder, 10 ins. diam., bears S.17°W., 28 lks. dist.,
marked $\frac{1}{2}$ S 5 B T.

Ascend 140 ft. on NW. slope.

62.60 Ridge, bears NW. and SE.; descend 200 ft. on NE. slope.

70.20 Ravine, course NE.; thence over N. slope.

72.20 Spur, slopes NE.; descend 125 ft. on E. slope.

76.75 Ravine, course NW.; ascend 210 ft. on W. slope.

82.40 Spur, slopes NW.; descend 50 ft. on NE. slope to

85.30 (Apportioned distance) Set an iron post, 3 ft. long, 2
ins. diam., 27 ins. in the ground, for re-established
cor. of secs. 32 and 33, T. 19 S., R. 9 W., with brass
cap marked

T19S	R9W
S32	S33
S5	
T20S R9W	
1921	

from which

An alder, 30 ins. diam., bears N.55°E., 57 lks. dist.,
marked T 19 S R 9 W S 33 B T.

A fir, 20 ins. diam., bears N.83°W., 34 lks. dist.,
marked T 19 S R 9 W S 32 B T.

N.86°14'E., resurveying S. bdy. of Sec. 33, T. 19 S., R.
9 W.

Over mountainous land, through heavy timber and dense
undergrowth.

Descend 300 ft. on NE. slope.

9.50 Ravine, course NE.; ascend 20 ft. on W. slope to

9.81 Point of intersection with line bet. secs. 4 and 5, de-
termined as hereinafter set forth.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in