

County Surveyor's Record, Douglas County, Oregon

Resurvey of Portion of North Bdy. of T. 20 S., R. 9 W.

CHAINS

the ground, for closing cor. of secs. 4 and 5, with brass cap marked

T19S	R9W
<u>S33</u>	
S5	S4
T20S	R9W
CC	
1921	

from which

A maple, 14 ins. diam., bears S.38°E., 27 lks.dist., marked T 20 S R 9 W S 4 C C B T.

An alder, 30 ins. diam., bears S.15°W., 61 lks.dist., marked T 20 S R 9 W S 5 C C B T.

Ascend 30 ft. on NW. slope.

- 13.25 Low spur, slopes N.; descend 50 ft. on NE. slope.
- 15.00 Ravine, course N.; ascend 325 ft. on W. slope.
- 27.90 Spur, slopes NW.; descend 150 ft. on NE. slope.
- 31.00 Ravine, course NE.; ascend 25 ft. on NW. slope.
- 33.00 Spur, slopes NE.; descend 270 ft. on NE. slope.
- 38.45 Creek, 8 lks. wide, course NW.; ascend 150 ft. on W. slope to
- 42.65 (Apportioned distance) Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for re-established $\frac{1}{4}$ sec. cor. of sec. 33 only, with brass cap marked

<u>$\frac{1}{4}$S33</u>
1921

from which

A fir, 40 ins. diam., bears N.32°E., 55 lks. dist., marked $\frac{1}{4}$ S 33 B T.

An alder, 8 ins. diam., bears N.70°W., 8 lks. dist., marked $\frac{1}{4}$ S 33 B T.

Ascend 250 ft. on W. slope to

- 50.10 Midpoint on N. slope of sec. 4, determined as hereinafter set forth.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 4 only, with brass cap marked

<u>$\frac{1}{4}$S4</u>
1921