

Resurvey of Portion of North Bdy. of T. 20 S., R. 9 W.

CHAINS

from which

An alder, 10 ins. diam., bears S.59°E., 18 lks.dist.,
marked $\frac{1}{4}$ S 4 B T.

A fir, 20 ins. diam., bears S.6°W., 21 lks. dist.,
marked $\frac{1}{4}$ S 4 B T.

Ascend 60 ft. on W. slope.

52.20 Spur, slopes SW.; ascend 80 ft. on SW. slope.

54.65 Ridge, bears NW. and SE.; descend 200 ft. on NE. slope.

58.00 Ravine, course N.; ascend 30 ft. on NW. slope.

64.00 Spur, slopes NE.; descend 210 ft. on NE. slope.

68.40 Ravine, course NE.

70.80 Creek, 4 lks. wide, course NW.; ascend 330 ft. on W.
slope to

85.30 (Apportioned distance) Set an iron post, 3 ft. long, 2
ins. diam., 27 ins. in the ground, for re-established
cor. of secs. 33 and 34, T. 19 S., R. 9 W., with brass
cap marked

T19S	R9W
S33	S34
T20S R9W	
S4	
1921	

from which

An alder, 12 ins. diam., bears N.20°E., 20 lks.dist.,
marked T 19 S R 9 W S 34 B T.

A fir, 30 ins. diam., bears N.31°W., 36 lks. dist.,
marked T 19 S R 9 W S 33 B T.

N.86°14'E., resurveying S. bdy. of Sec. 34, T. 19 S., R.
9 W.

Over mountainous land, through heavy timber and dense
undergrowth.

Ascend 30 ft. on SW. slope to

5.08 Point of intersection with line bet. secs. 3 and 4, de-
termined as hereinafter set forth.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in
the ground, for closing cor. of secs. 3 and 4, with