

County Surveyor's Record, Douglas County, Oregon

Resurvey of Portion of North Bdy. of T. 20 S., R. 9 W.

CHAINS

brass cap marked

T19S R9W
 S34
 S4 | S3
 T20S | R9W
 CC
 1921

from which

A fir, 8 ins. diam., bears S.75°E., 16 lks. dist.,
 marked T 20 S R 9 W S 3 C C B T.

A chittem, 8 ins. diam., bears S.16°W., 70 lks. dist.,
 marked T 20 S R 9 W S 4 C C B T.

Ascend 140 ft. on SW. slope.

8.10 Ridge, bears NW. and SE.; descend 625 ft. on NE. slope,
 to creek.

14.75 Ravine, course NE.

20.20 Ravine, course N.

24.20 Ravine, course N.

30.10 Creek, 3 lks. wide, course SE.; descend 60 ft. on SE.
 slope.

36.60 Moore Creek, 6 lks. wide, course SE.; ascend 150 ft. on
 SW. slope to

42.65 (Apportioned distance) Set an iron post, 3 ft. long, 1
 in. diam., 27 ins. in the ground, for re-established $\frac{1}{2}$
 sec. cor. of sec. 34 only, with brass cap marked

 $\frac{1}{2}$ S34
 1921

from which

A fir, 30 ins. diam., bears N.24°E., 28 lks. dist.,
 marked $\frac{1}{2}$ S 34 B T.

An alder, 20 ins. diam., bears N.70°W., 16 lks. dist.,
 marked $\frac{1}{2}$ S 34 B T.

Ascend 95 ft. on SW. slope to

45.17 (40.00 chs. easting from closing cor. of secs. 3 and 4).
 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in
 the ground, for $\frac{1}{2}$ sec. cor. of sec. 3 only, with brass
 cap marked

 $\frac{1}{2}$ S3
 1921