

Resurvey of Portion of North Bdy. of T. 20 S., R. 9 W.

CHAINS

from which

An alder, 14 ins. diam., bears S.80°E., 29 lks. dist.,
marked $\frac{1}{4}$ S 3 B T.

An alder, 10 ins. diam., bears S.7°W., 34 lks. dist.,
marked $\frac{1}{4}$ S 3 B T.

Ascend 315 ft. on W. slope.

58.50 Ridge, bears NW. and SE.; descend 280 ft. on NE. slope.

71.80 Ravine, course N.; ascend 140 ft. on NW. slope.

79.75 Spur, slopes N.; descend 195 ft. on E. slope.

83.95 Ravine, course NE.; thence over N. slope.

85.30 Intersect the cor. of secs. 34 and 35, T. 19 S., R. 9 W.,

which is a decayed fir post, marked and witnessed as
described by the surveyor general, except that no
bearing tree is found in Sec. 34. The old post is no
longer fit for monument, therefore, at exact corner
point.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the
ground, for cor. of secs. 34 and 35, T. 19 S., R. 9 W.,
with brass cap marked

T19S	R9W
S34	S35
T20S R9W	
S3	
1921	

from which

(Old bearing tree) A fir, 30 ins. diam., bears N.55 $\frac{1}{2}$ °
E., 20 lks. dist., marked T 19 S R 9 W S 35 B T.

(New bearing tree) A maple, 18 ins. diam., bears
N.43°W., 90 lks. dist., marked T 19 S R 9 W S 34
B T.

Thence East, resurveying N. bdy. of Sec. 3.

Ascend 25 ft. on NW. slope.

0.85 Intersect the cor. of secs. 2 and 3, position determined
by reference to the bearing trees, which are as de-
scribed by the surveyor general, no trace of the old
post found; at exact corner point

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in