

Resurvey of Portion of North Bdy. of T. 20 S., R. 9 W.

CHAINS

the ground, for cor. of secs. 2 and 3, with brass cap marked

T19S R9W	
S35	
S32	S2
T20S	R9W
1921	

from which (old bearing trees)

A hemlock, 24 ins. diam., bears S.19 $\frac{1}{2}$ °E., 11 lks. dist., marked T 20 S R 9 W S 2 B T.

A fir, 28 ins. diam., bears S.81°W., 52 lks. dist., marked T 20 S R 9 W S 3 B T.

Retracement and Resurvey of Subdivision Lines of T. 20 S., R. 9 W. by Fred Mensch, U. S. Cadastral Engineer, under special instructions dated Apr. 8, 1920. Group 56.

From the cor. of secs. 10, 11, 14, and 15, N.0°03'E., retracing W. bdy. of Sec. 11.

39.83 The  $\frac{1}{2}$  sec. cor. bears East, 17 lks. dist.

77.85 Fall 37 lks. W. of cor. of secs. 2, 3, 10, and 11.

The bearing and length of the south half of this line is N.0°18'E., 39.83 chs.; and of the north half, N.0°21'E., 38.02 chs.

From the cor. of secs. 2, 3, 10, and 11, N.0°03'E., retracing W. bdy. of sec. 2.

45.06 The  $\frac{1}{2}$  sec. cor. bears West, 4 lks. dist.

84.64 Fall 33 lks. W. of the cor. of secs. 2 and 3, on N. bdy. of the Tp.

The bearing and length of the south half of this line is North, 45.06 chs.; and of the north half, N.0°34'E., 39.58 chs.

From the cor. of secs. 10, 11, 14, and 15, S.89°52'W., retracing the line bet. secs. 10 and 15.

40.04 The  $\frac{1}{2}$  sec. cor. bears North, 52 lks. dist.

80.10 Fall 69 lks. S. of the cor. of secs. 9, 10, 15, and 16.

The bearing and length of the east half of this line is N.89°23'W., 40.04 chs.; and of the west half, N.89°53'W., 40.06 chs.