

Retracement and Resurvey of Subdivision Lines
of T. 20 S., R. 9 W.

CHAINS

From the cor. of secs. 9, 10, 15, and 16,
N.89°50'W., retracing line bet. secs. 9 and 16.

39.11 The $\frac{1}{2}$ sec. cor. bears North, 3.79 chs. dist.

78.76 Fall 3.67 chs. S. of the cor. of secs. 8, 9, 16, and 17.
The bearing and length of the east half of this line is
N.84°18'W., 39.30 chs.; and of the West half, West,
39.65 chs.

From the cor. of secs. 8, 9, 16, and 17.
N.89°42 $\frac{1}{2}$ 'W., retracing line bet. secs. 8 and 17.

39.45 The $\frac{1}{2}$ sec. cor. bears South, 49 lks. dist.

78.85 Fall 37 lks. N. of the cor. of secs. 7, 8, 17, and 18.
The bearing and length of the east half of this line is
S.89°35'W., 39.45 chs.; and of the west half, N.89°32'W.,
39.40 chs.

From the cor. of secs. 7, 8, 17, and 18.
S.89°29'W., retracing line bet. secs. 7 and 18.

39.89 The $\frac{1}{2}$ sec. cor. bears North, 96 lks. dist.

79.49 Fall 1.97 chs. S. of the cor. of secs. 7, 12, 13, and 18,
on W. bdy. of the Tp.
The bearing and length of the east half of this line is
N.89°08'W., 39.89 chs.; and of the west half, N.89°04'W.,
39.60 chs.

The point for cor. of secs. 10, 11, 14, and 15 is deter-
mined by reference to the NE. and SE. bearing trees;
no other evidence of the corner found; at exact corner
point
Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in
the ground, for cor. of secs. 10, 11, 14, and 15, with
brass cap marked

T20S	R9W
S10	S11
S15	S14
1921	

from which

(Old bearing tree) A fir, 48 ins. diam., bears
N.59 $\frac{1}{2}$ 'E., 62 lks. dist., marked T 20 S R 9 W S 11
B T.