

Resurvey of Subdivision Lines of T. 20 S., R. 9 W.

CHAINS

Thence.

N.0°21'E.

Ascend 110 ft. on S. slope.

3.00 Spur, slopes E.; descend 50 ft. on NE. slope.

6.40 Spur, slopes NE.; descend 300 ft. on NW. slope.

15.15 Ravine, course NE.; ascend 290 ft. on SE. slope.

22.50 Spur, slopes E.; descend 350 ft. on NE. slope.

29.40 Creek, 1 lk. wide, course E.; ascend 325 ft. on S. slope,
to

38.02 Intersect the cor. of secs. 2, 3, 10, and 11, originally
a fir, 20 ins. diam., now dead and uprooted, marked and
witnessed as described by the surveyor general, except
that the NE. and SE. bearing trees are dead and down,
and the NW. bearing tree is dead. At exact corner
point, in cavity of uprooted corner tree,

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in
the ground, for cor. of secs. 2, 3, 10, and 11, with
brass cap marked

T20S	R9W
S3	S2
S10	S11
1921	

from which

(New bearing tree) A vine maple, 4 ins. diam., bears
N.34°E., 28 lks. dist., marked T 20 S R 9 W S 2
B T.

(New bearing tree) A chittem, 5 ins. diam., bears
S.63°E., 56 lks. dist., marked T 20 S R 9 W S 11
B T.

(Old bearing tree) A fir, 36 ins. diam., bears
S.86°W., 27 lks. dist., marked T 20 S R 9 W S 10
B T.

(New bearing tree) A fir, 30 ins. diam., bears N.
42°W., 42 lks. dist., marked T 20 S R 9 W S 3
B T.