

County Surveyor's Record, Douglas County, Oregon

Resurvey of Subdivision Lines of T. 20 S., R. 9 W.

CHAINS

North, resurveying line bet. secs. 2 and 3.
Over mountainous land, through heavy timber and dense undergrowth.

Ascend 100 ft. on S. slope.

3.00 Spur, slopes E.; descend 420 ft. on N. slope.

14.60 Ravine, course NE.; ascend 100 ft. on SE. slope.

23.00 Spur, slopes NE.; descend 240 ft. on N. slope.

30.40 Moore Creek, 8 lks. wide, course SE.; ascend 215 ft. on SW. slope.

35.65 Spur, slopes SW.; descend 10 ft. on NW. slope.

38.11 Ravine, course SW.; ascend 80 ft. on S. slope to

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 3 only, with brass cap marked

$\frac{1}{4}$
S 3
1921

*FD. OK
6/18/22
D. P. ...
1192-28*

from which

A fir, 40 ins. diam., bears S.86°W., 36 lks. dist., marked $\frac{1}{4}$ S 3 B T.

A fir, 36 ins. diam., bears N.37°W., 88 lks. dist., marked $\frac{1}{4}$ S 3 B T.

Ascend 185 ft. on SW. slope to

45.06 Intersect true point for old $\frac{1}{4}$ sec. cor., determined by reference to the original bearing trees, which are as described by the surveyor general, except that the SE. bearing tree is dead; no trace of old post found. Hereafter, this cor. will refer to sec. 2 only. I obliterate marks on former bearing tree W. of line, and at exact corner point

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 2 only, with brass cap marked

$\frac{1}{4}$
S 2
1921

from which (new bearing trees)