

County Surveyor's Record, Douglas County, Oregon

Resurvey of Subdivision Lines of T. 20 S., R. 9 W.

CHAINS

39.65 Ravine, course NE.; ascend 15 ft. on E. slope to

40.04 Intersect true point for $\frac{1}{4}$ sec. cor., determined by reference to the original bearing trees, no trace of old post found; at exact corner point

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$$\frac{1}{4} \frac{S10}{S15}$$
 1921

from which (old bearing trees)

A cedar, 12 ins. diam., bears N.31 $\frac{1}{2}$ °E., 31 lks. dist., marked $\frac{1}{4}$ S 10 B T.

A maple, 12 ins. diam., bears S.87 $\frac{1}{2}$ °W., 66 lks. dist., marked $\frac{1}{4}$ S 15 B T.

Thence

N.89°53'W.

Ascend 240 ft. on E. slope.

6.10 Spur, slopes NE.; descend 25 ft. on NW. slope.

9.95 Ravine, course NE.; ascend 480 ft. on NE. slope.

22.20 Ridge, bears NW. and SE.; descend 150 ft. on SW. slope.

31.00 Ravine, course SE.; ascend 200 ft. on SE. slope.

38.00 Ridge, bears N. and S.; descend 60 ft. on SW. slope, to

40.06 Intersect the cor. of secs. 9, 10, 15, and 16, which is a fir, 40 ins. diam., marked and witnessed as described by the surveyor general, except that the SW. bearing tree is dead. I take new bearing tree.

From the corner

(Old bearing tree) A fir, 40 ins. diam., bears N.71°E., 46 lks. dist., marked T 20 S R 9 W S 10 B T.

(Old bearing tree) A fir, 18 ins. diam., bears S.40°E., 39 lks. dist., marked T 20 S R 9 W S 15 B T.

(New bearing tree) An alder, 8 ins. diam., bears S.61°W., 24 lks. dist., marked T 20 S R 9 W S 16 B T.

(Old bearing tree) A fir, 40 ins. diam., bears N.19°