

## Resurvey of Subdivision Lines of T. 20 S., R. 9 W.

CHAINS

W., 36 lks. dist., marked T 20 S R 9 W S 9 B T.

N.84°18'W., resurveying line bet. secs. 9 and 16.

Over mountainous land, through heavy timber and dense undergrowth.

Descend 260 ft. on SW. slope.

10.00 Creek, 2 lks. wide, course SW.

11.50 Crane Creek, 6 lks. wide, course S.; ascend 240 ft. on E. slope.

17.80 Ridge, bears NW. and SE.; descend 570 ft. on SW. slope, to

39.30 Intersect the old  $\frac{1}{4}$  sec. cor., which is a sandstone, 5x8x7 ins. above ground, firmly set, marked and witnessed as described by the surveyor general. Hereafter, this cor. will refer to sec. 16 only. I obliterate marks on N. face of stone, and mark  $\frac{1}{4}$  on S. face; also obliterate marks on former bearing tree N. of line, and take new bearing tree.

From the corner

(New bearing tree) A vine maple, 6 ins. diam., bears

S.25°E., 30 lks. dist., marked  $\frac{1}{4}$  S 16 B T.

(Old bearing tree) A fir, 45 ins. diam., bears

S.16°W., 13 lks. dist., marked  $\frac{1}{4}$  S 16 B T.

Thence

West

Descend 40 ft. on W. slope, to

0.89 Point at 40.00 chs. westing from cor. of secs. 9, 10, 15, and 16.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor. of sec. 9 only, with brass cap marked189

1921

from which

A chittem, 8 ins. diam., bears N.4°E., 103 lks.

dist., marked  $\frac{1}{4}$  S 9 B T.