

Resurvey of Subdivision Lines of T. 20 S., R. 9 W.

CHAINS

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 8 and 9, with brass cap marked

T20S	R9W
S8	S9
S17	
T20S R9W	
1921	

from which

A fir, 6 ins. diam., bears N.60°E., 16 lks. dist., marked T 20 S R 9 W S 9 B T.

A fir, 36 ins. diam., bears N.25°W., 36 lks. dist., marked T 20 S R 9 W S 8 B T.

Thence bet. secs. 8 and 17.

- 1.70 Ridge, divide bet. Coon and Johnson Creeks, bears NW. and SE.; descend 140 ft. on W. slope.
 - 5.75 Ravine, course SW.; ascend 85 ft. on SE. slope.
 - 11.00 Spur, slopes S.; descend 460 ft. on W. slope.
 - 23.55 Branch of Johnson Creek, 6 lks. wide, course SW.; ascend 135 ft. on SE. slope.
 - 27.00 Spur, slopes SE.; thence over S. slope..
 - 28.00 Ravine, course SE.; ascend 210 ft. on E. slope.
 - 34.40 Spur, slopes S.; descend 60 ft. on SW. slope, to
 - 39.45 Intersect true point for old $\frac{1}{4}$ sec. cor., determined by reference to the original bearing trees, which are as described by the surveyor general, no trace of old post found. Hereafter, this cor. will refer to sec. 17 only. I obliterate marks on former bearing tree referring to sec. 8, and at exact corner point
- Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 17 only, with brass cap marked

$\frac{1}{4}$ S17
1921

from which

(Old bearing tree) A fir, 40 ins. diam., bears S.10° E., 19 lks. dist., marked $\frac{1}{4}$ S 17 B T.