

Resurvey of Subdivision Lines of T. 20 S., R. 9 W.

CHAINS

bears S.50°E., 22 lks. dist., marked T 20 S R 9
W S 17 B T.

(Old bearing tree) An alder, 30 ins. diam., bears
S.89°W., 40 lks. dist., marked T 20 S R 9 W S 18
B T.

N.89°08'W., resurveying the N. bdy. of sec. 18.

Over mountainous land, through heavy timber and dense
undergrowth.

Descend 25 ft. on SW. slope, to

- 2.39 Point at 80.00 chs. westing from cor. of secs. 8 and 9.
Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in
the ground, for cor. of secs. 7 and 8, with brass cap
marked

T20S	R9W
S7	S8
S18	
1921	

from which

A maple, 18 ins. diam., bears N.61°E., 23 lks. dist.,
marked T 20 S R 9 W S 8 B T.

A vine maple, 8 ins. diam., bears N.32°W., 23 lks.
dist., marked T 20 S R 9 W S 7 B T.

Thence bet. secs. 7 and 18.

Descend 220 ft. on NW. slope.

- 10.95 Ravine, course NW.; descend 25 ft. on NW. slope.
11.85 Ravine, course SW.; descend 25 ft. on SW. slope.
15.15 Branch of Johnson Creek, 5 lks. wide, course S.; ascend
365 ft. on E. slope.
25.35 Spur, slopes NE.; descend 60 ft. on NW. slope.
27.75 Ravine, course NE.; ascend 180 ft. on E. slope.
32.85 Ridge, bears NW. and SE.; descend 100 ft. on SW. slope.
36.00 Ravine, course SW.; thence over S. slope.
39.89 Intersect the old $\frac{1}{4}$ sec. cor., originally a vine maple,
3 ins. diam., now nearly obliterated by decay, witness-
ed as described by the surveyor general. Hereafter