

## Resurvey of Subdivision Lines of T. 20 S., R. 9 W.

CHAINS

this cor. will refer to sec. 18 only. I obliterate marks on former bearing tree N. of line, and at exact corner point, in cavity of decayed corner tree

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor. of sec. 18 only, with brass cap marked

 $\frac{1}{4}$ S18

1921

from which

(Old bearing tree) A fir, 40 ins. diam., bears

S.76°E., 100 lks. dist., marked  $\frac{1}{4}$  S 18 B T.

(New bearing tree) A hemlock, 14 ins. diam., bears

S.78°W., 50 lks. dist., marked  $\frac{1}{4}$  S 18 B T.

Thence

N.89°04'W.

2.50 Point at 40.00 chs. westing from cor. of secs. 7 and 8.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor. of sec. 7 only, with brass cap marked

 $\frac{1}{4}$ S7

1921

from which

A fir, 18 ins. diam., bears N.14°E., 16 lks. dist., marked  $\frac{1}{4}$  S 7 B T.

A fir, 24 ins. diam., bears N.55°W., 29 lks. dist., marked  $\frac{1}{4}$  S 7 B T.

Descend 440 ft. on NW. slope.

15.25 Ravine, course SW.

15.55 Johnson Creek, 5 lks. wide, course S.; ascend 560 ft. on SE. slope.

39.60 Intersect the cor. of secs. 7, 12, 13, and 18, on W. bdy. of the Tp., heretofore described.