

Subdivision of T. 20 S., R. 9 W. as surveyed by Fred Mensch, U. S. Cadastral Engineer, under special instructions dated April 8, 1920. Group 56.

CHAINS

From the cor. of secs. 2, 3, 10 and 11,  
West, on sectional correction line, setting temp. cors.  
at intervals of 40.00 chs.  
331.32 To intersection with re-established W. bdy. of the Tp.,  
at 12.03 chs. N.10°17'W. of cor. of secs. 1 and 12, T.  
20 S., R. 10 W.

From the cor. of secs. 9, 10, 15, and 16, heretofore de-  
scribed,  
N.0°18'E., on a random line, for distance, bet. secs. 9  
and 10.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

77.34 Intersect sectional correction line, 40 lks. W. of temp.  
sec. cor.; at the point of intersection  
Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in  
the ground, for cor. of secs. 3, 4, 9, and 10, with  
brass cap marked

T20S	R9W
34	33
39	310
1921	

from which

A cedar, 18 ins. diam., bears N.33°E., 38 lks. dist.,  
marked T 20 S R 9 W S 3 B T.

A cedar, 18 ins. diam., bears S.57°E., 60 lks. dist.,  
marked T 20 S R 9 W S 10 B T.

A chittem, 10 ins. diam., bears S.74°W., 74 lks. dist.,  
marked T 20 S R 9 W S 9 B T.

A chittem, 12 ins. diam., bears N.38°W., 62 lks. dist.,  
marked T 20 S R 9 W S 4 B T.

Thence

S.0°18'W., on a true line, bet. secs. 9 and 10.

Over mountainous land, through heavy timber and dense  
undergrowth.

Ascend 530 ft. on NW. slope.

19.25 Spur, slopes NE.; descend 390 ft. on S. slope.

27.50 Ravine, course E.; ascend 135 ft. on N. slope.