

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 20 S., R. 9 W.

CHAINS

- 30.00 Spur, slopes E.; descend 110 ft. on SE. slope.
- 33.50 Ravine, course NE.; ascend 200 ft. on NW. slope, to
- 37.34 Set an iron post, 3 ft. long, 1 in. diam.;, 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 10 only, with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ | \\ S10 \\ 1921 \end{array}$$

from which

An alder, 9 ins. diam., bears N.80°E., 9 lks. dist., marked $\frac{1}{4}$ S 10 B T.

An alder, 8 ins. diam., bears S.22°E., 38 lks. dist., marked $\frac{1}{4}$ S 10 B T.

Ascend 100 ft. on NW. slope, to

- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 9 only, with brass cap marked.

$$\begin{array}{c} \frac{1}{4} \\ | \\ S9 \\ 1921 \end{array}$$

from which

A fir, 36 ins. diam., bears S.70°W., 57 lks. dist., marked $\frac{1}{4}$ S 9 B T.

A fir, 24 ins. diam., bears N.83°W., 62 lks. dist., marked $\frac{1}{4}$ S 9 B T.

Ascend 45 ft. on NW. slope.

- 41.30 Spur, slopes E.; descend 200 ft. on SE. slope.
- 49.70 Ravine, course NE.; ascend 180 ft. on N. slope.
- 52.90 Spur, slopes NE.; descend 95 ft. on SE. slope.
- 57.10 Ravine, course E.; ascend 420 ft. on NE. slope.
- 66.35 Ridge, bears NW. and SE.; descend 135 ft. on SW. slope, to
- 77.34 The cor. of secs. 9, 10, 15, and 16.

From the cor. of secs. 2, 3, 10, and 11, heretofore described,

West, on true sectional correction line, bet. secs. 3 and 10.