

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 20 S., R. 9 W.

CHAINS

Over mountainous land, through heavy timber and dense undergrowth.

Descend 100 ft. on SW. slope.

2.90 Draw, course SE.; ascend 60 ft. on E. slope.

6.90 Spur, slopes SE.; thence over S. slope.

9.00 Ravine, course SE.; ascend 240 ft. on E. slope.

20.70 Ridge, bears NE. and SW.; descend 525 ft. on NW. slope.

33.90 Creek, 1 lk. wide, course SW.; ascend 30 ft. on SE. slope.

37.90 Ravine, course SE.; ascend 75 ft. on NE. slope, to

40.20 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$ $\frac{S3}{S10}$
 1921

from which

A yew, 18 ins. diam., bears N.58°W., 51 lks. dist., marked $\frac{1}{4}$ S 3 B T.

A fir, 18 ins. diam., bears S.32°W., 18 lks. dist., marked $\frac{1}{4}$ S 10 B T.

Ascend 140 ft. on E. slope.

43.50 Spur, slopes S.; descend 200 ft. on SW. slope.

54.40 Creek, 3 lks. wide, course SW.; ascend 50 ft. on SE. slope.

55.90 Spur, slopes SE.; descend 250 ft. on W. slope.

68.75 Creek, 10 lks. wide, course S.; ascend 100 ft. on SE. slope.

71.00 Spur, slopes SE.; descend 30 ft. on SW. slope.

76.45 Creek, 5 lks. wide, course SE.; ascend 30 ft. on NE. slope, to

80.40 The cor. to secs. 3, 4, 9, and 10, heretofore described.

North, on a true line, bet. secs. 3 and 4.

Over mountainous land, through heavy timber and dense undergrowth.

0.23 Creek, 3 lks. wide, course NE.; thence over bench.

1.55 Creek, 4 lks. wide, course SE.; ascend 440 ft. on SW. slope.