

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 20 S., R. 9 W.

CHAINS

- 15.50 Ridge, bears NW. and SE.; descend 390 ft. on NE. slope.
- 28.30 Creek, 2 lks. wide, course SE.; ascend 250 ft. on S. slope.
- 34.75 Spur, slopes E.; descend 145 ft. on NE. slope to $\frac{1}{2}$ sec. cor.
- 38.40 Ravine, course E.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{2}$ sec. cor., with brass cap marked
- $\frac{1}{2}$
 S4 | S3
 1921
- from which
- A fir, 40 ins. diam., bears S.35°E., 35 lks. dist., marked $\frac{1}{2}$ S 3 B T.
- A fir, 40 ins. diam., bears N.84°W., 33 lks. dist., marked $\frac{1}{2}$ S 4 B T.
- Descend 70 ft. on NE. slope.
- 46.10 Creek, 3 lks. wide, course SE.; ascend 630 ft. on SW. slope.
- 71.00 Junction of ridges, bear NE., SE., and SW.; descend 130 ft. on NW. slope, to
- 79.47 Intersect N. bdy. of Tp., 5.08 chs. N.86°14'E. of the cor. of secs. 33 and 34, T. 19 S., R. 9 W., and set closing cor., heretofore described.

From the cor. of secs. 8 and 9, on N. bdy. of Sec. 17, heretofore described,

N.0°17'E., on a random line, for distance, bet. secs. 8 and 9.

- 40.00 Set temp. $\frac{1}{2}$ sec. cor.
- 73.26 Intersect sectional correction line, 58 lks. W. of temp. sec. cor.; at the point of intersection
- Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 4, 5, 8, and 9, with brass cap marked

T20S | R9W
 S5 | S4

 S8 | S9
 1921