

Subdivision of T. 20 S., R. 9 W.

CHAINS

from which

An alder, 12 ins. diam., bears N.89°E., 26 lks. dist.,
marked T 20 S R 9 W S 4 B T.

An alder, 6 ins. diam., bears S.54½°E., 36 lks. dist.,
marked T 20 S R 9 W S 9 B T.

An alder, 8 ins. diam., bears S.58°W., 11 lks. dist.,
marked T 20 S R 9 W S 8 B T.

A fir, 40 ins. diam., bears N.30°W., 35 lks. dist.,
marked T 20 S R 9 W S 5 B T.

Thence

S.0°17'W., on a true line, bet. secs. 8 and 9.

Over mountainous land, through heavy timber and dense
undergrowth.

Descend 230 ft. on SE. slope.

5.85 Creek, 1 lk. wide, course SW.; descend 15 ft. on SW. slope.

7.10 Coon Creek, 2 lks. wide, course SE.; ascend 60 ft. on NE.
slope.

12.85 Top of rise; descend 210 ft. on SE. slope.

27.45 Ravine, course SE.; ascend 200 ft. on NE. slope.

40.00 Spur, slopes NE.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in
the ground, for ¼ sec. cor., with brass cap marked

$\frac{1}{4}$
 SS | S9
 1921

from which

A fir, 30 ins. diam., bears N.89°E., 19 lks. dist.,
marked ¼ S 9 B T.

A fir, 4 ins. diam., bears S.59°W., 16 lks. dist.,
marked ¼ S 8 B T.

Descend 25 ft. on SE. slope.

42.70 Draw, course E.; ascend 110 ft. on NE. slope.

46.70 Ridge, bears E. and W.; descend 135 ft. on S. slope.

50.50 Ravine, course E.; ascend 95 ft. on NE. slope.

55.35 Spur, slopes E.; descend 50 ft. on SE. slope.

57.75 Ravine, course E.; ascend 250 ft. on NE. slope.