

Subdivision of T. 20 S., R. 9 W.

CHAINS

- 69.10 Spur, slopes SE.; descend 100 ft. on SE. slope, to
73.26 The cor. of secs. 8 and 9, on N. bdy. of Sec. 17.
-
- From the cor. of secs. 3, 4, 9, and 10, heretofore described,
West, on true sectional correction line, bet. secs. 4 and 9.
Over mountainous land, through heavy timber and dense undergrowth.
- 0.22 Creek, 2 lks. wide, course NE.; ascend 465 ft. on SE. slope.
- 17.60 Spur, slopes NE.; descend 45 ft. on NW. slope.
- 19.30 Head of ravine, course NW.; ascend 25 ft. on NE. slope.
- 21.55 Spur, slopes NW.; descend 170 ft. on NW. slope.
- 26.75 Ravine, course NE.; ascend 300 ft. on SE. slope, to
40.09 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
- $$\frac{1}{4} \frac{S4}{S9}$$
 1921
- from which
- A maple, 7 ins. diam., bears N.62°E., 27 lks. dist., marked $\frac{1}{4}$ S 4 B T.
- A fir, 40 ins. diam., bears S.72°E., 46 lks. dist., marked $\frac{1}{4}$ S 9 B T.
- Ascend 160 ft. on E. slope.
- 43.15 Ridge, bears N. and S.; descend 65 ft. on NW. slope.
- 45.00 Creek, 2 lks. wide, course N.; ascend 230 ft. on NE. slope.
- 51.50 Ridge, bears NW. and SE.; descend 135 ft. on SW. slope.
- 59.55 Ravine, course NW.; ascend 155 ft. on NE. slope.
- 63.50 Ridge, bears NW. and SE.; descend 380 ft. on SW. slope.
- 77.00 Creek, 1 lk. wide, course SW.; ascend 70 ft. on SE. slope, to
80.18 The cor. to secs. 4, 5, 8, and 9, heretofore described.

N.0°01'W., on a true line, bet. secs. 4 and 5.