

## County Surveyor's Record, Douglas County, Oregon

## Subdivision of T. 20 S., R. 9 W.

CHAINS

73.22

Intersect sectional correction line, 68 lks. W. of temp. sec. cor.; at the point of intersection

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 5, 6, 7, and 8, with brass cap marked

T20S	R9W
S6	S5
S7	S8
1921	

from which

An alder, 14 ins. diam., bears N.72°E., 27 lks. dist., marked T 20 S R 9 W S 5 B T.

An alder, 20 ins. diam., bears S.21°E., 30 lks. dist., marked T 20 S R 9 W S 8 B T.

A vine maple, 6 ins. diam., bears S.12°W., 13 lks. dist., marked T 20 S R 9 W S 7 B T.

A fir, 10 ins. diam., bears N.12°W., 62 lks. dist., marked T 20 S R 9 W S 6 B T.

Thence

S.0°17'W., on a true line, bet. secs. 7 and 8.

Over mountainous land, through heavy timber and dense undergrowth.

Ascend 50 ft. on NW. slope.

1.00 Spur, slopes W.; descend 50 ft. on SW. slope.

5.85 Creek, 1 lk. wide, course SW.; ascend 270 ft. on N. slope.

12.80 Ridge, bears E. and W.; descend 260 ft. on S. slope.

22.75 Ravine, course SE.; ascend 20 ft. on NE. slope.

24.60 Spur, slopes SE.; descend 365 ft. on SE. slope.

36.30 Creek, 3 lks. wide, course SW.; ascend 100 ft. on NW. slope, to

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked

S7	S8
1921	

from which

A fir, 40 ins. diam., bears S.55°E., 23 lks. dist., marked  $\frac{1}{4}$  S 8 B T.