

Subdivision of T. 20 S., R. 9 W.

CHAINS

A maple, 28 ins. diam., bears S.28°W., 25 lks. dist.,
marked $\frac{1}{4}$ S 7 B T.

Ascend 100 ft. on NW. slope.

44.00 Top of rise; thence over W. slope.

49.00 Begin descent, 245 ft. on S. slope.

56.40 Ravine, course W.; ascend 330 ft. on NW. slope.

64.40 Spur, slopes W.; descend 320 ft. on S. slope.

71.60 Ravine, course W.; ascend 80 ft. on NW. slope, to

73.22 The cor. of secs. 7 and 8, on N. bdy. of Sec. 18.

From the cor. of secs. 4, 5, 8, and 9, heretofore de-
scribed,

West, on true sectional correction line, bet. secs. 5
and 8.

Over mountainous land, through heavy timber and dense
undergrowth.

Ascend 65 ft. on SE. slope.

1.70 Spur, slopes S.; descend 115 ft. on SW. slope.

4.45 Ravine, course SW.

5.10 Coon Creek, 2 lks. wide, course SE.; ascend 300 ft. on
NE. slope.

13.00 Ridge, bears N. and S.; descend 200 ft. on NW. slope.

17.85 Ravine, course NW.; ascend 50 ft. on NE. slope.

22.00 Spur, slopes N.; descend 135 ft. on NW. slope.

25.75 Creek, 3 lks. wide, course NE.; ascend 160 ft. on SE.
slope.

31.50 Ridge, bears N. and S.; descend 260 ft. on SW. slope, to

40.05 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in
the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$ S5
38
1921

from which

A fir, 40 ins. diam., bears N.74°W., 47 lks. dist.,
marked $\frac{1}{4}$ S 5 B T.

A fir, 40 ins. diam., bears S.70°W., 62 lks. dist.,
marked $\frac{1}{4}$ S 8 B T.