

Subdivision of T. 20 S., R. 9 W.

CHAINS

Descend 110 ft. on SW. slope.

42.70 Ravine, course NW.; ascend 70 ft. on E. slope.

47.34 Spur, slopes N.; descend 110 ft. on NW. slope.

49.75 Ravine, course NE.; ascend 430 ft. on SE. slope.

64.35 Spur, slopes NE.; descend 120 ft. on NW. slope.

68.50 Ravine, course N.; ascend 140 ft. on NE. slope.

74.90 Ridge, bears NE. and SW.; descend 235 ft. on NW. slope, to

80.10 The cor. of secs. 5, 6, 7, and 8, heretofore described.

West, on true sectional correction line, bet. secs. 6
and 7.

Over mountainous land, through heavy timber and dense
undergrowth.

Descend 180 ft. on SW. slope.

7.00 Ravine, course NW.; thence over N. slope.

10.70 Spur, slopes NW.; descend 30 ft. on W. slope.

12.20 Ravine, course N.; ascend 130 ft. on E. slope.

15.40 Spur, slopes NW.; descend 100 ft. on SW. slope.

20.00 Ravine, course NW.; ascend 185 ft. on E. slope.

25.70 Spur, slopes NW.; descend 410 ft. on SW. slope.

38.65 Creek, 3 lks. wide, course NW.; ascend 50 ft. on E.
slope, to

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in
the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked.

$\frac{1}{4}$ S6.
 $\frac{1}{4}$ S7
1921

from which

A hemlock, 14 ins. diam., bears N.30°E., 71 lks.
dist., marked $\frac{1}{4}$ S 6 B T.

A cedar, 24 ins. diam., bears S.10°W., 32 lks. dist.,
marked $\frac{1}{4}$ S 7 B T.

Ascend 300 ft. on E. slope.

48.70 Ridge, bears N. and S.; descend 160 ft. on W. slope.

52.45 Draw, course N.; ascend 80 ft. on NE. slope.

55.70 Spur, slopes N.; descend 160 ft. on NW. slope.