

County Surveyor's Record, Douglas County, Oregon

West Bdy. of T. 19 S., R. 8 W.
 Survey by Charles M. Collier under Contract 580 dated
 June 23, 1891

CHAINS

Proceeded to NW. cor. of T. 20 S., R. 8 W., which is a post about 6 inches sq., standing 4 ft. above ground, marked T 19 S R 8 W S 31 on NE., T 20 S R 8 W S 6 on SE., T 20 S R 9 W S 1 on SW., T 19 S R 9 W S 36 on NW. faces, with 6 notches on each edge; from which

A fir, 36 ins. diam., bears N.48°E., 23 lks. dist., marked T 19 S R 8 W S 31 B T.

A fir, 20 ins. diam., bears S.7°E., 43 lks. dist., marked T 20 S R 8 W S 6 B T.

A hemlock, 9 ins. diam., bears S.80°W., 37 lks. dist., marked T 20 S R 9 W S 1 B T.

A fir, 30 ins. diam., bears N.53°W., 72 lks. dist., marked T 19 S R 9 W S 36 B T.

N. on W. bdy. of Sec. 31.
 Va. observed at 2 p.m. 20°30'.

Descend steep, through heavy fir timber.

3.75 Enter a bottom, c.E. & W.

5.00 Stream, 25 lks. wide, c W., rocky bed.

6.25 Trail, c E. & W.; a house within garden brs. about NE., about 10 chs. dist., not visible from line.

7.50 Fir, 30 ins. diam.

9.00 Rise gradually.

26.00 Stream, 4 lks. wide, c S.30°E.

26.20 Stream, 3 lks. wide, c S.3°E.

28.50 Leave stream from N.20°W.

40.00 Fir, 24 ins. diam., which I mark for $\frac{1}{2}$ sec. cor., $\frac{1}{4}$ S on W. face; from which

A fir, 40 ins. diam., bears N.76°E., 16 lks. dist., marked $\frac{1}{4}$ S B T.

A fir, 36 ins. diam., bears N.69°W., 25 lks. dist., marked $\frac{1}{4}$ S B T.

46.00 Top of gentle ascent on ridge, 400 ft. up, c E. & W.; descend very steep.

53.25 Fir, 24 ins. diam., foot of steep descent, 250 ft. down; descend more gently.