

County Surveyor's Record, Douglas County, Oregon

West Bdy. of T. 19 S., R. 8 W.

CHAINS

to secs. 19 & 30, T. 19 S R 8 W S 19 on NE., T 19 S R 8 W S 30 on SE. faces, with 4 notches on N. and 2 notches on S. edges; from which

A maple, 10 ins. diam., bears N.57°E., 29 lks. dist., marked T 19 S R 8 W S 19 B T.

A maple, 8 ins. diam., bears S.39½°E., 15 lks. dist., marked T 19 S R 8 W S 30 B T.

Aug. 26th, '91.

N. on W. boundary Sec. 19.

Va. observed at 8 a.m. 20°30'E.

Ascend over rolling ground in fine timber.

- 7.25 Spring, 4 lks. wide, c SE.
- 18.60 Fir, 36 ins. diam.
- 22.50 Va. at 8h 30m a.m. observed 20°15'E.
- 25.00 Top of ascent; thence along East slope; enter deadening, 400 ft. above cor.
- 40.00 Set post, 4 ft. long, 4 ins. sq., 24 ins. in the ground, for ¼ sec. cor., marked ¼ S on W. face; dug pits, 18x18x12 ins., E. & W. of post, 5½ ft. dist.; and raised mound of earth, 1½ ft. high, 3½ ft. base, around post. No live trees in limits.
- 41.00 Descend very steep; enter green timber.
- 52.25 Into little bottom, cleaned out by recent slide, 400 ft. down.
- 54.00 Stream, 5 lks. wide, c East.
- 56.00 Stream, 8 lks. wide, c S.20°E.; thence along up E. side of said stream.
- 65.00 Same stream, 8 lks. wide, c S.20°W.
- 70.00 Same stream, 8 lks. wide, c S.20°E.
- Ascend steep West slope.
- 72.85 Fir, 60 ins. diam.
- 80.00 Fir, 6 ins. diam., which I mark for cor. to secs. 18 & 19, T 19 S R 8 W S 18 on NE., T 19 S R 8 W S 19 on SE. faces, with 3 notches on N. & S. edges; from which