

## County Surveyor's Record, Douglas County, Oregon

West Bdy. of T. 19 S., R. 8 W.

CHAINS

A fir, 10 ins. diam., bears N.44 $\frac{1}{2}$ °E., 48 lks. dist.,  
marked T 19 S R 8 W S 7 B T.

A fir, 10 ins. diam., bears S.20°E., 42 lks. dist.,  
marked T 19 S R 8 W S 18 B T.

N. on W. bdy. of Sec. 7.

Observed va. 20°15'E. at 9 a.m.

- 1.00 Top of high ridge, extending West and Northeast from  
"The Two High Buttes"; this is by far the highest ridge  
touched in Tps. 19 S., Rs. 7 & 8 W.  
Descend gently in fine green timber.
- 10.00 Descend steep.
- 14.00 Along W. side of hollow; descend.
- 36.50 Stream, 5 lks. wide, c N.30°W., 600 ft. down from ridge;  
ascend gently.
- 40.00 Set post, 4 ft. long, 4 ins. sq., 24 ins. in the ground,  
marked  $\frac{1}{4}$  S on W. face; from which  
A fir, 30 ins. diam., bears S.33°E., 24 lks. dist.,  
marked  $\frac{1}{4}$  S B T.  
A fir, 15 ins. diam., bears N.40°W., 60 lks. dist.,  
marked  $\frac{1}{4}$  S B T.  
Thence in partial deadening.
- 48.00 Fir, 40 ins. diam.
- 53.25 Stream, 3 lks. wide, c W.
- 56.95 Fir, 24 ins. diam.; descend gently.
- 75.00 Into head of little hollow, c N.20°E.
- 78.50 Fir, 36 ins. diam.
- 80.00 Set post, 4 ft. long, 4 ins. sq., 24 ins. in the ground,  
for cor. to secs. 6 & 7, marked T 19 S R 8 W S 6 on NE.,  
T 19 S R 8 W S 7 on SE. faces, with 1 notch on N. and  
5 notches on S. edges; from which  
A fir, 40 ins. diam., bears N.16 $\frac{1}{2}$ °E., 32 lks. dist.,  
marked T 19 S R 8 W S 6 B T.  
A fir, 40 ins. diam., bears S.43 $\frac{1}{2}$ °E., 50 lks. dist.,  
marked T 19 S R 8 W S 7 B T.

See page  
for West  
Bdy. Sec.  
6, T. 19 S.  
R. 8 W.

Sept. 24th, '91.