

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 19 S., R. 9 W.
Survey by Henry L. Chandler under Contract No. 705 dated
April 14th, 1899.

CHAINS

I begin at the cor. of secs. 31 and 32, on S. bdy. of
Tp., previously established by me,
Thence I run
N.0°01'E., bet. secs. 31 and 32.
Ascend through burnt timber and dense undergrowth.

9.00 Top of spur, 150 ft. above sec. cor., bears NE.; descend
200 ft. to

30.96 Spring branch, 2 lks. wide, course NE.; ascend.

40.00 The $\frac{1}{4}$ sec. cor., established on former survey, which is a
post, 3 ft. long, 3 ins. sq., set 24 ins. in the ground,
marked $\frac{1}{4}$ S 31 on W. and 32 on E. faces; from which
An alder, 7 ins. diam., bears N.16°W., 20 lks. dist.,
marked $\frac{1}{4}$ S B T.
An alder, 6 ins. diam., bears N.6°E., 9 lks. dist.,
marked $\frac{1}{4}$ S B T.

.62.25 Top of spur, 200 ft. above creek, bears NE.; descend 150
ft. to

.80.00 The cor. of secs. 29, 30, 31 & 32, established on former
survey, which is a basalt stone, 12x8x8 ins., 8 ins.
in the ground, marked with 1 notch on S. and 5 notches
on E. edges; from which
An alder, 10 ins. diam., bears N.30°E., 27 lks. dist.,
marked T 19 S R 9 W S 29 B T.
An alder, 10 ins. diam., bears S.18°E., 11 lks. dist.,
marked T 19 S R 9 W S 32 B T.
An alder, 9 ins. diam., bears S.9°W., 23 lks. dist.,
marked T 19 S R 9 W S 31 B T.
An alder, 5 ins. diam., bears N.7°W., 15 lks. dist.,
marked T 19 S R 9 W S 30 B T.

Aug. 12, 1899.

W., on a random line, bet. secs. 30 & 31.

40.00 Set a temp. $\frac{1}{4}$ sec. cor.

80.02 Intersect the E. boundary of T. 19 S., R. 10 W. at a
point 9.16 chs. N. of the cor. of secs. 25 and 36, and