

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 19 S., R. 9 W.

CHAINS

ground, for  $\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$  S 19 on N. and 30 on S. faces; from which

An alder, 4 ins. diam., bears N.25°E., 14 lks.dist., marked  $\frac{1}{4}$  S B T.

An alder, 4 ins. diam., bears S.40°W., 23 lks.dist., marked  $\frac{1}{4}$  S B T.

Old cor. bears S.79°E., 13 lks. dist.; I destroy it.

62.75 Top of spur, 150 ft. above last ravine, bears SW.; descend 100 ft. to

72.05 Ravine, course SW.; ascend.

79.88 The cor. of secs. 19, 20, 29 & 30.

Aug. 13, 1899.

N.0°01'E., bet. secs. 19 and 20.

Descend through timber and dense undergrowth.

17.20 Ravine, 100 ft. below sec. cor., course SW.; ascend 200 ft. to

24.25 Top of spur, bears W.; descend.

40.00 The  $\frac{1}{4}$  sec. cor. established on former survey, which is a post, 3 ft. long, 3 ins. sq., set 24 ins. in the ground, marked  $\frac{1}{4}$  S 19 on W. and 20 on E. faces; from which

A fir, 6 ins. diam., bears N.80°E., 7 lks.dist., marked  $\frac{1}{4}$  S B T.

A fir, 8 ins. diam., bears S.12°W., 43 lks. dist., marked  $\frac{1}{4}$  S B T.

52.05 Creek, 2 lks. wide, 150 ft. below spur, course W.; ascend 150 ft. to

70.00 Top of spur, bears W.; descend.

80.00 The cor. of secs. 17, 18, 19 and 20, established on former survey, which is a post, 3 ft. long, 4 ins. sq., set 24 ins. in the ground, marked T 19 S S 17 on NE., R 9 W S 20 on SE., S 19 on SW. and S 18 on NW. faces, with 3 notches on S. and 5 notches on E. edges; from which

A fir, 12 ins. diam., bears N.46°E., 30 lks. dist.,