

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 19 S., R. 9 W.

CHAINS

marked T 19 S R 9 W S 17 B T.

A fir, 12 ins. diam., bears S.76 $\frac{1}{2}$ °E., 29 lks. dist.,

marked T 19 S R 9 W S 20 B T.

A fir, 7 ins. diam., bears S.11°W., 51 lks. dist.,

marked T 19 S R 9 W S 19 B T.

A fir, 7 ins. diam., bears N.17°W., 39 lks. dist.,

marked T 19 S R 9 W S 18 B T.

W., on a random line, bet. secs. 18 & 19.

40.00 Set a temp. $\frac{1}{4}$ sec. cor.

80.02 Intersect the E. bdy. of Tp. 19 S., R. 10 W., at a point
9.30 chs. N. of the cor. of secs. 13 and 24, and at
point of intersection

Set a basalt stone, 16x8x6 ins., 12 ins. in the ground,
for closing cor. of secs. 18 & 19, marked C C on E.
face, with 3 grooves on N. and S. faces; from which

A fir, 14 ins. diam., bears N.15°E., 26 lks. dist.,
marked T 19 S R 9 W S 18 B T.

A fir, 6 ins. diam., bears S.29°E., 20 lks. dist.,
marked T 19 S R 9 W S 19 B T.

Thence I run

E., on a true line, bet. secs. 18 & 19.

Descend through timber and dense undergrowth.

22.10 The N. fork of Smith River, 50 lks. wide, 200 ft. below
sec. cor., course SW.; ascend.

40.01 Set a fir post, 3 ft. long, 3 ins. sq., 24 ins. in the
ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S 8 on N. and 19 on
S. faces; from which

A fir, 4 ins. diam., bears N.70°E., 19 lks. dist.,
marked $\frac{1}{4}$ S B T.

A fir, 5 ins. diam., bears S.3°W., 21 lks. dist.,
marked $\frac{1}{4}$ S B T.

Old cor. bears S. 10 lks. dist.; I destroy it.

44.00 Top of spur, 250 ft. above river, bears SW.; descend 200
ft. to