

## Subdivisions of T. 19 S., R. 9 W.

CHAINS

71.00 Ravine, course SW.; ascend.

80.02 The cor. of secs. 17, 18, 19 &amp; 20.

N.0°01'E., bet. secs. 17 and 18.

Descend through timber and dense undergrowth.

6.00 Ravine, 100 ft. below sec. cor., course W.; ascend.

40.00 Set a fir post, 3 ft. long, 3 ins. sq., 24 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$  S 17 on W. & 18 on E. faces; from whichA fir, 6 ins. diam., bears N.60°W., 29 lks. dist., marked  $\frac{1}{4}$  S B T.A fir, 5 ins. diam., bears S.46°E., 10 lks. dist., marked  $\frac{1}{4}$  S B T.

Old cor. bears W., 15 lks. dist.; I destroy it.

60.50 Summit of ridge, 400 ft. above ravine, bears E. and W.; descend 300 ft. to

80.00 Set a sandstone, 16x10x6 ins., 12 ins. in the ground, for cor. of secs. 7, 8, 17 &amp; 18, marked with 4 notches on S. and 5 notches on E. edges; from which

A fir, 6 ins. diam., bears N.22°E., 4 lks. dist., marked T 19 S R 9 W S 8 B T.

A fir, 6 ins. diam., bears S.49°E., 51 lks. dist., marked T 19 S R 9 W S 17 B T.

A hemlock, 15 ins. diam., bears S.40°W., 33 lks. dist., marked T 19 S R 9 W S 18 B T.

A fir, 12 ins. diam., bears N.75°W., 13 lks. dist., marked T 19 S R 9 W S 7 B T.

Old cor. bears S.25°W., 30 lks. dist.; I destroy it.

Aug. 14, 1899.

W., on a random line, bet. secs. 7 &amp; 18.

40.00 Set a temp.  $\frac{3}{4}$  sec. cor.

79.84 Intersect the E. bdy. of T. 19 S., R. 10 W., at a point 9.40 chs. N. of the cor. of secs. 12 &amp; 13, and at point of intersection