

Subdivisions of T. 19 S., R. 9 W.

CHAINS

- A hemlock, 7 ins. diam., bears N.76°W., 40 lks. dist., marked $\frac{1}{2}$ S B T.
- Old cor. bears S.60°E., 150 lks. dist.; I destroy it.
- 43.40 Creek, 12 lks. wide, 225 ft. below spur, course NW.; thence over bottom land.
- 47.00 Leave bottom, bears E. and W.; ascend 200 ft. to
- 59.00 Top of spur, bears NW.; descend.
- 64.25 Old cor. bears E., 5.50 chs. dist.; I destroy it.
- 67.00 L. Larson's cabin bears W., about 15.00 chs. dist.
- 76.00 Enter bottom land, 250 ft. below spur, bears NE. & SW.
- 80.00 A hemlock, 7 ins. diam., for cor. of secs. 5, 6, 7 & 8, I mark T 19 S S 5 on NE., R. 9 W S 8 on SE., S 7 on SW. and S 6 on NW. sides, with 5 notches on S. and E. sides; from which
- A hemlock, 7 ins. diam., bears N.67°E., 31 lks. dist., marked T 19 S R 9 W S 5 B T.
- A hemlock, 9 ins. diam., bears S.55°E., 27 lks. dist., marked T 19 S R 9 W S 8 B T.
- A hemlock, 7 ins. diam., bears S.15°W., 22 lks. dist., marked T 19 S R 9 W S 7 B T.
- A hemlock, 7 ins. diam., bears N.79°W., 44 lks. dist., marked T 19 S R 9 W S 6 B T.
-
- W., on a random line, bet. secs. 6 & 7.
- 40.00 Set temp. $\frac{1}{4}$ sec. cor.
- 79.74 Intersect E. bdy. of T. 19 S., R. 10 W., at a point 9.50 chs. N. of the cor. of secs. 1 and 12, and at point of intersection
- Set a sandstone, 16x12x6 ins., 12 ins. in the ground, for closing cor. of secs. 6 and 7, marked C C on E. face, with 5 notches on S. and 1 notch on N. edges; from which
- A fir, 40 ins. diam., bears N.56°E., 260 lks. dist., marked T 19 S R 9 W S 6 B T.
- A dead fir, 16 ins. diam., bears S.78°E., 14 lks.