

## Subdivisions of T. 19 S., R. 9 W.

CHAINS

ground, for  $\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$  S 29 on N. and 32 on S. faces; from which

A fir, 10 ins. diam., bears N.12°E., 16 lks. dist., marked  $\frac{1}{4}$  S B T.

A fir, 5 ins. diam., bears S.80°E., 17 lks. dist., marked  $\frac{1}{4}$  S B T.

Old cor. bears S., 6 lks. dist.; I destroy it.

57.25 Top of spur, 200 ft. above creek, bears SW.; descend 150 ft. to

71.00 Ravine, course SW.; ascend.

80.20 The cor. of secs. 28, 29, 32 & 33.

N.0°02'E., bet. secs. 28 and 29.

Descend through timber, partly dead, and dense undergrowth.

7.00 Ravine, 100 ft. below sec. cor., course SW.; ascend 200 ft. to

18.50 Top of spur, bears SW.; descend 150 ft. to

30.90 Ravine, course SW.; ascend.

40.00 Set a fir post, 3 ft. long, 3 ins. sq., 24 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$  S 29 on W. and 28 on E. faces; from which

A fir, 6 ins. diam., bears N.71°E., 31 lks. dist., marked  $\frac{1}{4}$  S B T.

A fir, 7 ins. diam., bears N.4°W., 1 lks. dist., marked  $\frac{1}{4}$  S B T.

Old cor. bears W., 16 lks. dist.; I destroy it.

46.00 Top of spur, 150 ft. above last ravine, bears W.; descend 200 ft. to

80.00 Set a sandstone, 12x8x8 ins., 8 ins. in the ground, for cor. of secs. 20, 21, 28 & 29, marked with 2 notches on S. and 4 notches on E. edges; from which

A fir, 6 ins. diam., bears N.50°E., 20 lks. dist., marked T 19 S R 9 W S 21 B T.

A fir, 6 ins. diam., bears S.70°E., 80 lks. dist., marked T 19 S R 9 W S 28 B T.